



## 181/182/183 FAST DRY SERIES

### PRODUCT DESCRIPTION:

**Description/Colors:** 181 Red / 182 Blue / 183 Green

**Benefits:** No tracking after 30 minutes. No visual tracking 30-60 seconds at 160°F maximum in the heat exchanger and 135°F-150°F at the spray nozzle.

**Finish/usage:** Flat Sheen

**Type:** 100% Acrylic Resin System, High Solids formulated for hot and cold applications.

**Limitations:** Do not apply at air, surface or product temperatures below 50°F (10°C) for best results.

### SPECIFICATION:

**Surfaces Recommended to Paint:** Centerlines and Edge Lines on roads, Highways, Crosswalks, Stop Zones, Parking lots, Storage Zones and Aisles, etc.

**Surface Preparation:** Surface must be clean, dry, and free from dirt, wax, grease, loose or peeling paint and other foreign material.

**In-Service Surface Temperature Limits:** Dry: 50°F (10°C) minimum. Immersion service: NOT RECOMMENDED. Avoid frost, fog and damp conditions.

**Federal Specifications:** Meets performance standards of Federal Specification TT-P1952E, Type II.

**Application Equipment:** Apply with brush, roller, Airless or conventional equipment.

**Thinning:** Use this product as provided, Do Not Thin.

**Recommended Application:** Theoretical spread rate: 300 linear feet X 4 inch per Gallon or 100 square feet per gallon at 16 mils wet. Coverage figures do not include surface irregularities due to porosity, spray loss or material loss when mixing.

**Recommended Wet Film per coat:** 14 to 16 mils. **Recommended Dry Film per coat:** 8 to 9 mils.

**Dry Time at 77°F & 50% Relative Humidity:** Dries to touch in 5-10 minutes. Drying times variable depending on temperature, air circulation and humidity.

**Clean Up:** Clean application equipment promptly with warm soapy water.

**Flash Point:** N/A Waterborne product.

**Packaging:** U.S. measure – 1 gallon (3.78L); 5 gallon (181.9L); 55 gallon (208L); 250 gallon (946.25L)

**WARNING:** Consult MSDS Sheet before using this paint. Paint can be harmful if swallowed. Keep from heat, fire and flames.

**Material Safety Data Sheet available upon request.**

### TYPICAL ANALYSIS – WHITE ONLY

Solids by Weight:	74.58 +/- 3%
Solids by Volume:	56.11 +/- 3%
V.O.C.:	96g per liter
Weight per Gallon:	14.17 +/- 0.3 pounds per gallon
Viscosity:	88-90 KU
Max V.O.C.:	100g per Liter

American Traffic Products, Inc. warrants that its products will conform and perform in accordance with the product specification sheets. American Traffic Products, Inc. also warrants its products to be free from defects in material and manufacturing. American Traffic Products, Inc.'s liability to the buyer or any third party for any losses or damages shall not exceed beyond replacement cost, excluding freight and handling of material, proven to be defective. American Traffic Products, Inc. agrees to respond to claims of defective material upon receipt of written notification and verification of product defect. Any claim must be made within five days of the discovery of the defect. In no event shall the seller be liable for any consequential or incidental damages or loss of profits. American Traffic Products, Inc. is not liable for variation in environment, application, color or changes in procedure, which may cause unsatisfactory results.